

November 25, 2021

**REQUEST FOR QUOTATIONS "RFQ" NO. PS20211423
SUPPLY AND DELIVERY OF DECORATIVE ROADWAY LIGHTS**

ADDENDUM NO. 1

RE: APPENDIX 1 - REQUIREMENTS - 3.0 SPECIFICATIONS - 3.1.7 LIGHTING LIST AND SPECIFICATIONS TABLE:

PLEASE ADD:

LIGHTING LIST AND SPECIFICATIONS TABLE (list of current and required models):

(see attached)

END OF ADDENDUM No. 1

NAME OF VENDOR

SIGNATURE OF AUTHORIZED SIGNATORY

DATE

Jessica Li
Buyer

APPENDIX 1 - REQUIREMENTS - SECTION 3.0 SPECIFICATIONS

LIGHTING LIST AND SPECIFICATIONS TABLE (list of current and required models):

| Item | CURRENT MAKE/MODEL (Currently used by COV) | EXISTING QUANTITY | Estimated Year 1 QTY | Estimated Year 2 QTY | Estimated Year 3 QTY | Estimated Year 4 QTY | 1-4 Year Total QTY | STYLE | REQUIRED MODEL (or approved equivalent), to replace existing model(s) | Total Qty | DESCRIPTION |
|------|---|----------------------|----------------------------|----------------------------|----------------------------|----------------------------|--------------------------|------------------|---|-----------|--|
| 1 | King Luminaire K204 HPS | 36 | 27 | 5 | 2 | 2 | 36 | Teardrop Pendant | King Luminaire K205 | 173 | K205 housing, 40W, 60W, 75W, 100W, and 120W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, shallow glass & flat (no lens) options, black colour housing, c/w KPL10-KPL11 plumbizer to fit onto existing arms and provide NEMA 7-pin receptacle. Exact models to be determined once simulations are complete. Dimensions: 25-1/4" height, 14-1/8" width. |
| | King Luminaire K205 HPS | 124 | 93 | 19 | 6 | 6 | 124 | | | | |
| | 79 AR HPS | 13 | 13 | 0 | 0 | 0 | 13 | | | | |
| 2 | Village Master - Kingsway HPS | 91 | 36 | 36 | 9 | 9 | 91 | Pendant | King Luminaire K809 | 91 | K809 housing, 40W, 60W, 75W, 100W, and 120W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, flat (no lens), black colour housing, c/w KPL20 plumbizer to fit onto existing arms and provide NEMA 7-pin receptacle. Exact models to be determined once simulations are complete. Dimensions: 21-1/2" height, 20-13/16" width. |
| 3 | Marine HPS | 49 | 0 | 20 | 15 | 15 | 49 | Marine Pendant | King Luminaire K206 | 49 | K206 housing, 40W, 60W, 75W, 100W, and 120W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, shallow glass lens, custom NEMA colour housing, c/w KPL10 plumbizer to fit onto existing arms, NEMA 7-pin receptacle to be mounted on pole by COV. Exact models to be determined once simulations are complete. Dimensions: 27-1/16" height, 27" width. |
| 4 | Lumec Domus 200W HPS | 27 | 27 | 0 | 0 | 0 | 27 | Pendant | Lumec Domus DMS50 | 27 | DMS50 housing, 69-131W LED engine options, 2700 & 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, flat lens, housing colour in green (to match existing), c/w luminaire adapter to fit onto existing threaded tube NEMA 7-pin receptacle included on fixture if possible. Exact models to be determined once simulations are complete. Dimensions: 488mm height 698mm width. |
| 5 | Globes HPS | 49 | 20 | 15 | 7 | 7 | 49 | Post-Top | King Luminaire K584 | 114 | K584 housing, 40W, 60W, 75W, 100W, and 120W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, shallow glass lens, custom NEMA colour housing, NEMA 7-pin receptacle included on fixture. Exact models to be determined once simulations are complete. Dimensions: 42-3/4" height, 20-3/8" width. |
| | Cube HPS | 65 | 26 | 20 | 10 | 10 | 65 | | | | |
| 6 | Post Top Hat HPS | 440 | 176 | 132 | 66 | 66 | 440 | Post-Top | Holophane (AEL) 245L | 440 | 245L Style "A" housing, 23-77W LED engine options, 2700 & 3000K CCT options, R2, R3, R4 optic options, 120-277V dimmable driver, "Rain pattern" acrylic lens, housing colour in standard grey, NEMA 7-pin receptacle included on fixture. Exact models to be determined once simulations are complete. Dimensions: 622mm height, 559mm width. |
| 7 | Invue Icon 250W HPS/MH | 23 | 23 | 0 | 0 | 0 | 23 | Side Mount | Invue Icon ICM | 23 | Icon ICM housing, 75-150W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, housing colour in black, NEMA 7-pin receptacle included on fixture. Exact models to be determined once simulations are complete. Dimensions: 881mm length, 633mm width. |
| 8 | Schreder Citea HPS/MH | 38 | 38 | 0 | 0 | 0 | 38 | Side Mount | Cyclone Celeste CR22SA | 210 | CR22SA side-mount housing, 60-100W LED engine options, 3000K CCT, Type 2, 3, and 4 optic options, clear lens, 120-277V dimmable driver, housing colour in blue and grey (custom RAL) depending on area, NEMA 7-pin receptacle included on top fixture. Exact models to be determined once simulations are complete. Dimensions: 580mm length, 220mm height |
| | Circa HPS | 60 | 30 | 30 | 0 | 0 | 60 | | | | |
| | Holophane Pachina HPS/MH | 112 | 112 | 0 | 0 | 0 | 112 | | | | |