

December 1, 2021

**REQUEST FOR QUOTATIONS “RFQ” No. PS20211423  
SUPPLY AND DELIVERY OF DECORATIVE ROADWAY LIGHTS**

**AMENDMENT No. 1**

**RE: APPENDIX 1 - REQUIREMENTS - 3.0 SPECIFICATIONS**

**3.1.4 Mounting**

*CURRENTLY READS:*

- (a) “Luminaires must be able to be mounted as specified in Section 4.0 - Drawing. A pendant luminaires shall be designed to attach to plumbizers and/or arms.”

*REPLACE WITH:*

- (a) “Luminaires must be able to be mounted as specified in **Appendix 1 - Lighting List and Specifications Table, “Description” column.** A pendant luminaires shall be designed to attach to plumbizers and/or arms.” - See attached

**RE: APPENDIX 1 - REQUIREMENTS - 3.0 SPECIFICATIONS**

**3.1.7 Lighting List and Specifications Table (list of current and required models)**

*DELETE IN ITS ENTIRETY:*

“Lighting List and Specifications Table (list of current and required models)” that was attached to Addendum No. 1

*REPLACE WITH:*

“Lighting List and Specifications Table (list of current and required models)” - (updated) - See attached

**RE: QUOTATIONS FORM - 1.0 TABLE OF PRICES**

*DELETE IN ITS ENTIRETY:*

“Appendix 3 - Pricing Tables A to C”

*REPLACE WITH:*

“Appendix 3 - Pricing Tables 1 to 3” (updated)

**All other conditions and specifications remain unchanged.**

---

**NAME OF VENDOR**

---

**SIGNATURE OF AUTHORIZED SIGNATORY**

---

**DATE**

Jessica Li, Buyer

## APPENDIX 1 - REQUIREMENTS - SECTION 3.0 SPECIFICATIONS

## LIGHTING LIST AND SPECIFICATIONS TABLE (list of current and required models):

Item	CURRENT MAKE/MODEL (Currently used by COV)	EXISTING QUANTITY	Estimated Year 1 QTY	Estimated Year 2 QTY	Estimated Year 3 QTY	Estimated Year 4 QTY	1-4 Year Total QTY	STYLE	REQUIRED MODEL (or approved equivalent), to replace existing model(s)	Total Qty	DESCRIPTION	Nominal Lumen Outputs	Mounting Details
1	King Luminaire K204 HPS	36	27	5	2	2	36	Teardrop Pendant	King Luminaire K205	173	K205 housing, 40W, 60W, 75W, 100W, and 120W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, shallow glass & flat (no lens) options, black colour housing, c/w KPL10-KPL11 plumbizer to fit onto existing arms and provide NEMA 7-pin receptacle. Exact models to be determined once simulations are complete. Dimensions: 25-1/4" height, 14-1/8" width.	5000 7000 8600 10700 13000	Mounts to 2" NPT thread on existing arm, pointing down.
	King Luminaire K205 HPS	124	93	19	6	6	124						
	79 AR HPS	13	13	0	0	0	13						
2	Village Master - Kingsway HPS	91	36	36	9	9	91	Pendant	King Luminaire K809	91	K809 housing, 40W, 60W, 75W, 100W, and 120W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, flat (no lens), black colour housing, c/w KPL20 plumbizer to fit onto existing arms and provide NEMA 7-pin receptacle. Exact models to be determined once simulations are complete. Dimensions: 21-1/2" height, 20-13/16" width.	5000 7000 8600 10700 13000	Mounts to 2-3/8" OD horizontal tenon on existing arm.
3	Marine HPS	49	0	20	15	15	49	Marine Pendant	King Luminaire K206	49	K206 housing, 40W, 60W, 75W, 100W, and 120W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, shallow glass lens, custom NEMA colour housing, c/w KPL10 plumbizer to fit onto existing arms, NEMA 7-pin receptacle to be mounted on pole by COV. Exact models to be determined once simulations are complete. Dimensions: 27-1/16" height, 27" width.	5000 7000 8600 10700 13000	Mounts to 2" NPT thread on existing arm, pointing down.
4	Lumec Domus 200W HPS	27	27	0	0	0	27	Pendant	Lumec Domus DMS50	27	DMS50 housing, 69-131W LED engine options, 2700 & 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, flat lens, housing colour in green (to match existing), c/w luminaire adapter to fit onto existing threaded tube NEMA 7-pin receptacle included on fixture if possible. Exact models to be determined once simulations are complete. Dimensions: 488mm height 698mm width.	8000 10000 12000 14000 18000	Existing tube size unknown. Include adapter cost if LED model has different mounting requirements than original DMS50 HID model.
5	Globes HPS	49	20	15	7	7	49	Post-Top	King Luminaire K584	114	K584 housing, 40W, 60W, 75W, 100W, and 120W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, shallow glass lens, custom NEMA colour housing, NEMA 7-pin receptacle included on fixture. Exact models to be determined once simulations are complete. Dimensions: 42-3/4" height, 20-3/8" width.	5000 7000 8600 10700 13000	Mounts to 2-3/8" to 3" OD vertical tenon on existing pole.
	Cube HPS	65	26	20	10	10	65						
6	Post Top Hat HPS	440	176	132	66	66	440	Post-Top	Holophane (AEL) 245L	440	245L Style "A" housing, 23-77W LED engine options, 2700 & 3000K CCT options, R2, R3, R4 optic options, 120-277V dimmable driver, "Rain pattern" acrylic lens, housing colour in standard grey, NEMA 7-pin receptacle included on fixture. Exact models to be determined once simulations are complete. Dimensions: 622mm height, 559mm width.	2500 3800 4200 6400 7300	Mounts to 2-3/8" to 3" OD vertical tenon on existing pole.
7	Invue Icon 250W HPS/MH	23	23	0	0	0	23	Side Mount	Invue Icon ICM	23	Icon ICM housing, 75-150W LED engine options, 3000K CCT, R2, R3, R4 optic options, 120-277V dimmable driver, housing colour in black, NEMA 7-pin receptacle included on fixture. Exact models to be determined once simulations are complete. Dimensions: 881mm length, 633mm width.	8500 11000 14000 17000	Fixture to mount to existing Invue Icon Slide Arm.
8	Schreder Citea HPS/MH	38	38	0	0	0	38	Side Mount	Cyclone Celeste CR225A	210	CR225A side-mount housing, 60-100W LED engine options, 3000K CCT, Type 2, 3, and 4 optic options, clear lens, 120-277V dimmable driver, housing colour in blue and grey (custom RAL) depending on area, NEMA 7-pin receptacle included on top fixture. Exact models to be determined once simulations are complete. Dimensions: 580mm length, 220mm height	6000 8000 10000	Mounts to 2-3/8" OD horizontal tenon on existing arm.
	Circa HPS	60	30	30	0	0	60						
	Holophane Pachina HPS/MH	112	112	0	0	0	112						